

Package ‘ClusterGVis’

June 17, 2025

Title One-Step to Cluster and Visualize Gene Expression Data

Version 0.1.3

Description Streamlining the clustering and visualization of time-series gene expression data from RNA-Seq experiments, this tool supports fuzzy c-means and k-means clustering algorithms. It is compatible with outputs from widely-used packages such as 'Seurat', 'Monocle', and 'WGCNA', enabling seamless downstream visualization and analysis. See Lokesh Kumar and Matthias E Futschik (2007) <[doi:10.6026/97320630002005](https://doi.org/10.6026/97320630002005)> for more details.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

LazyDataCompression xz

RoxygenNote 7.3.2

Depends R (>= 2.10)

Imports Biobase, circlize, clusterProfiler, colorRamps, ComplexHeatmap, dplyr, e1071, factoextra, ggplot2, grDevices, grid, magrittr, Matrix, methods, purrr, BiocManager, reshape2, scales, SingleCellExperiment, stats, SummarizedExperiment, TCseq, tibble

Suggests igraph, knitr, monocle, pheatmap, rmarkdown, Seurat, WGCNA, utils

biocViews

clusterProfiler, SummarizedExperiment, ComplexHeatmap, circlize, SingleCellExperiment, TCseq

URL <https://github.com/junjunlab/ClusterGVis/>,
<https://junjunlab.github.io/ClusterGvis-manual/>

BugReports <https://github.com/junjunlab/ClusterGVis/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Jun Zhang [aut, cre] (ORCID: <<https://orcid.org/0000-0001-7692-9105>>)

Maintainer Jun Zhang <3219030654@stu.cpu.edu.cn>

Repository CRAN

Date/Publication 2025-06-17 04:20:09 UTC

Contents

BEAM_res	2
cell_data_set	3
check_dependency	3
clusterData	4
enrichCluster	6
exprs	8
exprs,cell_data_set-method	8
exprs	9
filter.std modified by Mfuzz filter.std	9
getClusters	10
net	11
normalized_counts	11
plot_genes_branched_heatmap2	12
plot_multiple_branches_heatmap2	14
plot_pseudotime_heatmap2	15
prepareDataFromscRNA	17
pre_pseudotime_matrix	18
pseudotime	19
pseudotime,cell_data_set-method	19
sig_gene_names	20
size_factors	20
termanno	21
termanno2	21
traverseTree	22
visCluster	22
Index	27

BEAM_res	<i>This is a test data for this package test data description</i>
----------	---

Description

This is a test data for this package test data description

Usage

BEAM_res

Format

An object of class data.frame with 47192 rows and 8 columns.

Author(s)

JunZhang

cell_data_set	<i>The cell_data_set class from https://github.com/cole-trapnell-lab/monocle3/blob/master/R/cell_data_set.R</i>
---------------	---

Description

The main class used by Monocle3 to hold single-cell expression data. cell_data_set extends the Bioconductor SingleCellExperiment class.

Details

This class is initialized from a matrix of expression values along with cell and feature metadata.

Fields

reduce_dim_aux SimpleList, auxiliary information from reduced dimension.
principal_graph_aux SimpleList, auxiliary information from principal graph construction
principal_graph SimpleList of igraph objects containing principal graphs for different dimensionality reduction.
clusters SimpleList of cluster information for different dimensionality reduction.

check_dependency	<i>Check and Install Required Packages</i>
------------------	--

Description

This function checks if the required Bioconductor and CRAN packages are installed. If any of the required packages are not installed, it installs them automatically. This includes Bioconductor packages such as clusterProfiler, SummarizedExperiment, ComplexHeatmap, SingleCellExperiment, TCseq, monocle, and Biobase. It also checks for CRAN packages such as Seurat, WGCNA, igraph, pheatmap, circlize, e1071, and colorRamps.

Usage

```
check_dependency()
```

Value

NULL This function does not return a value. It installs the packages as needed.

clusterData

*Cluster Data Based on Different Methods***Description**

Cluster Data Based on Different Methods

Usage

```
clusterData(
  obj = NULL,
  scaleData = TRUE,
  cluster.method = c("mfuzz", "TCseq", "kmeans", "wgcn"),
  TCseq_params_list = list(),
  object = NULL,
  min.std = 0,
  cluster.num = NULL,
  subcluster = NULL,
  seed = 5201314,
  ...
)
```

Arguments

obj	An input object that can take one of two types: - A cell_data_set object for trajectory analysis. - A matrix or data.frame containing expression data.
scaleData	Logical. Whether to scale the data (e.g., z-score normalization).
cluster.method	Character. Clustering method to use. Options are one of "mfuzz", "TCseq", "kmeans", or "wgcn".
TCseq_params_list	A list of additional parameters passed to the <code>TCseq::timeclust</code> function.
object	A pre-calculated object required when using "wgcn" as the clustering method.
min.std	Numeric. Minimum standard deviation for filtering expression data.
cluster.num	Integer. The number of clusters to identify.
subcluster	A numeric vector of specific cluster IDs to include in the results. If NULL, all clusters are included.
seed	An integer seed for reproducibility in clustering operations.
...	Additional arguments passed to internal functions such as <code>pre_pseudotime_matrix</code> .

Details

Depending on the selected `cluster.method`, different clustering algorithms are used:

- "mfuzz": Applies Mfuzz soft clustering method, suitable for identifying overlapping clusters.

- "TCseq": Uses TCseq clustering for time-series expression data with support for additional parameters.
- "kmeans": Employs standard k-means clustering via base R's `stats::kmeans`.
- "wgcna": Leverages pre-calculated WGCNA (Weighted Gene Co-expression Network Analysis) networks.

The function is designed to be flexible, allowing preprocessing (e.g., filtering by `min.std`), scaling the data (`scaleData = TRUE`), and generating results compatible with data visualization pipelines.

Value

A list containing the following clustering results:

- **wide.res**: A wide-format data frame with clusters and normalized expression levels.
- **long.res**: A long-format data frame for visualizations, containing cluster information, normalized values, cluster names, and memberships.
- **cluster.list**: A list where each element contains genes belonging to a specific cluster.
- **type**: The clustering method used ("mfuzz", "TCseq", "kmeans", or "wgcna").
- **geneMode**: Currently set to "none" (reserved for future use).
- **geneType**: Currently set to "none" (reserved for future use).

WGCNA Clustering

If the **WGCNA** method is selected, the object parameter must contain a pre-calculated WGCNA network object. This is typically obtained using the WGCNA package functions.

Subsetting Clusters

Use the `subcluster` parameter to focus on specific clusters. Cluster IDs not included in the `subcluster` vector will be excluded from the final results.

Author(s)

JunZhang

This function performs clustering on input data using one of four methods: **mfuzz**, **TCseq**, **kmeans**, or **wgcna**. The clustering results include metadata, normalized data, and cluster memberships.

Examples

```
data("exps")

# kmeans
ck <- clusterData(obj = exps,
                  cluster.method = "kmeans",
                  cluster.num = 8)
```

enrichCluster

*Perform GO/KEGG Enrichment Analysis for Multiple Clusters***Description**

Perform GO/KEGG Enrichment Analysis for Multiple Clusters

Usage

```
enrichCluster(
  object = NULL,
  type = c("BP", "MF", "CC", "KEGG", "ownSet"),
  TERM2GENE = NULL,
  TERM2NAME = NULL,
  OrgDb = NULL,
  id.trans = TRUE,
  fromType = "SYMBOL",
  toType = c("ENTREZID"),
  readable = TRUE,
  organism = "hsa",
  pvalueCutoff = 0.05,
  topn = 5,
  seed = 5201314,
  add.gene = FALSE,
  use_internal_data = FALSE,
  heatmap.type = c("plot_pseudotime_heatmap2", "plot_genes_branched_heatmap2",
    "plot_multiple_branches_heatmap2"),
  ...
)
```

Arguments

object	An object containing clustering results. This is clusterData object. Alternatively, it can be a CellDataSet object, in which case the function can also visualize pseudotime data.
type	Character. The type of enrichment analysis to perform. Options include: • "BP": Biological Process (GO) • "MF": Molecular Function (GO) • "CC": Cellular Component (GO) • "KEGG": KEGG Pathway analysis • "ownSet": Custom gene set enrichment, requiring TERM2GENE and optionally TERM2NAME.
TERM2GENE	A data frame containing mappings of terms to genes. Required when type = "ownSet". This must be a two-column data frame, where the first column is the term and the second column is the gene.

TERM2NAME	A data frame containing term-to-name mappings. Optional when type = "ownSet". This must also be a two-column data frame, where the first column is the term and the second column is the name.
OrgDb	An organism database object (e.g., org.Hs.eg.db for human or org.Mm.eg.db for mouse), used for GO or KEGG enrichment analysis.
id.trans	Logical. Whether to perform gene ID transformation. Default is TRUE.
fromType	Character. The type of the input gene IDs (e.g., "SYMBOL", "ENSEMBL"). Default is "SYMBOL".
toType	Character. The target ID type for transformation using clusterProfiler::bitr (e.g., "ENTREZID"). Default is "ENTREZID".
readable	Logical. Whether to convert the enrichment result IDs back to a readable format (e.g., SYMBOL). Only applicable for GO and KEGG analysis. Default is TRUE.
organism	Character. The KEGG organism code (e.g., "hsa" for human, "mmu" for mouse). Required when performing KEGG enrichment. Default is "hsa".
pvalueCutoff	Numeric. The p-value cutoff for enriched terms to be included in the results. Default is 0.05.
topn	Integer or vector. The number of top enrichment results to extract. If a single value, it is applied to all clusters. Otherwise, it should match the number of clusters. Default is 5.
seed	Numeric. Seed for random operations to ensure reproducibility. Default is 5201314.
add.gene	Logical. Whether to include the list of genes associated with each enriched term in the results. Default is FALSE.
use_internal_data	Logical, use KEGG.db or latest online KEGG data for enrichKEGG function. Default is FALSE.
heatmap.type	Character. The type of heatmap visualization to use when input data is a CellDataSet object. Options include: • "plot_pseudotime_heatmap2" • "plot_genes_branched_heatmap2" • "plot_multiple_branches_heatmap2"
...	Additional arguments passed to plot_pseudotime_heatmap2/plot_genes_branched_heatmap2/plot_multiple_branches_heatmap2 functions.

Value

a data.frame.

Author(s)

JunZhang

This function performs Gene Ontology (GO) or KEGG enrichment analysis, or custom gene set enrichment, on clustered genes. It supports multiple clusters, incorporating cluster-specific results into its analysis.

exprs

Generic to access cds count matrix

Description

Generic to access cds count matrix

Usage

```
exprs(x)
```

Arguments

x A cell_data_set object.

Value

Count matrix.

Author(s)

<https://github.com/cole-trapnell-lab/monocle3>

exprs,cell_data_set-method*Method to access cds count matrix*

Description

Method to access cds count matrix

Usage

```
## S4 method for signature 'cell_data_set'  
exprs(x)
```

Arguments

x A cell_data_set object.

Value

Count matrix.

`exps`*This is a test data for this package test data description*

Description

This is a test data for this package test data description

Usage

```
exps
```

Format

An object of class `data.frame` with 3767 rows and 6 columns.

Author(s)

Junjun Lao

`filter.std` modified by `Mfuzz filter.std`
using `filter.std` to filter low expression genes

Description

using `filter.std` to filter low expression genes

Usage

```
filter.std(eset, min.std, visu = TRUE, verbose = TRUE)
```

Arguments

<code>eset</code>	expression matrix, default <code>NULL</code> .
<code>min.std</code>	min stand error, default 0.
<code>visu</code>	whether plot, default <code>FALSE</code> .
<code>verbose</code>	show filter information.

Value

matrix.

getClusters

Determine Optimal Clusters for Gene Expression or Pseudotime Data

Description

Determine Optimal Clusters for Gene Expression or Pseudotime Data

Usage

```
getClusters(obj = NULL, ...)
```

Arguments

obj	A data object representing the gene expression data or pseudotime data: • If the input is a <code>cell_data_set</code> object (e.g., from Monocle3), the function preprocesses the data using <code>pre_pseudotime_matrix</code>. • If the input is a numeric matrix or a <code>data.frame</code>, it directly uses this data. Default is <code>NULL</code>.
...	Additional arguments passed to the preprocessing function <code>pre_pseudotime_matrix</code> (e.g., <code>assays</code>, <code>normalize</code>, etc.).

Value

A ggplot object visualizing the Elbow plot, where:

- The x-axis represents the number of clusters tested.
- The y-axis represents the WSS for each cluster number.

The optimal cluster number can be visually identified at the "elbow point," where the reduction in WSS diminishes sharply.

a ggplot.

Author(s)

JunZhang

The `getClusters` function identifies the optimal number of clusters for a given data object. It supports multiple input types, including gene expression matrices and objects such as `cell_data_set`. The function implements the Elbow method to evaluate within-cluster sum of squares (WSS) across a range of cluster numbers and visualizes the results.

net	<i>This is a test data for this package test data description</i>
-----	---

Description

This is a test data for this package test data description

Usage

```
net
```

Format

An object of class `list` of length 10.

Author(s)

Junjun Lao

normalized_counts	<i>Return a size-factor normalized and (optionally) log-transformed expression</i>
-------------------	--

Description

Return a size-factor normalized and (optionally) log-transformed expression

Usage

```
normalized_counts(
  cds,
  norm_method = c("log", "binary", "size_only"),
  pseudocount = 1
)
```

Arguments

cds	A CDS object to calculate normalized expression matrix from.
norm_method	String indicating the normalization method. Options are "log" (Default), "binary" and "size_only".
pseudocount	A pseudocount to add before log transformation. Ignored if norm_method is not "log". Default is 1.

Value

Size-factor normalized, and optionally log-transformed, expression matrix.

Author(s)

<https://github.com/cole-trapnell-lab/monocle3>

matrix

plot_genes_branched_heatmap2

Create a heatmap to demonstrate the bifurcation of gene expression along two branches which is slightly modified in monocle2

Description

@description returns a heatmap that shows changes in both lineages at the same time. It also requires that you choose a branch point to inspect. Columns are points in pseudotime, rows are genes, and the beginning of pseudotime is in the middle of the heatmap. As you read from the middle of the heatmap to the right, you are following one lineage through pseudotime. As you read left, the other. The genes are clustered hierarchically, so you can visualize modules of genes that have similar lineage-dependent expression patterns.

Usage

```
plot_genes_branched_heatmap2(
  cds_subset = NULL,
  branch_point = 1,
  branch_states = NULL,
  branch_labels = c("Cell fate 1", "Cell fate 2"),
  cluster_rows = TRUE,
  hclust_method = "ward.D2",
  num_clusters = 6,
  hmcols = NULL,
  branch_colors = c("#979797", "#F05662", "#7990C8"),
  add_annotation_row = NULL,
  add_annotation_col = NULL,
  show_rownames = FALSE,
  use_gene_short_name = TRUE,
  scale_max = 3,
  scale_min = -3,
  norm_method = c("log", "vstExprs"),
  trend_formula = "~sm.ns(Pseudotime, df=3) * Branch",
  return_heatmap = FALSE,
  cores = 1,
  ...
)
```

Arguments

<code>cds_subset</code>	CellDataSet for the experiment (normally only the branching genes detected with <code>branchTest</code>)
<code>branch_point</code>	The ID of the branch point to visualize. Can only be used when <code>reduceDimension</code> is called with <code>method = "DDRTree"</code> .
<code>branch_states</code>	The two states to compare in the heatmap. Mutually exclusive with <code>branch_point</code> .
<code>branch_labels</code>	The labels for the branches.
<code>cluster_rows</code>	Whether to cluster the rows of the heatmap.
<code>hclust_method</code>	The method used by pheatmap to perform hierarchical clustering of the rows.
<code>num_clusters</code>	Number of clusters for the heatmap of branch genes
<code>hmcols</code>	The color scheme for drawing the heatmap.
<code>branch_colors</code>	The colors used in the annotation strip indicating the pre- and post-branch cells.
<code>add_annotation_row</code>	Additional annotations to show for each row in the heatmap. Must be a dataframe with one row for each row in the <code>fData</code> table of <code>cds_subset</code> , with matching IDs.
<code>add_annotation_col</code>	Additional annotations to show for each column in the heatmap. Must be a dataframe with one row for each cell in the <code>pData</code> table of <code>cds_subset</code> , with matching IDs.
<code>show_rownames</code>	Whether to show the names for each row in the table.
<code>use_gene_short_name</code>	Whether to use the short names for each row. If <code>FALSE</code> , uses row IDs from the <code>fData</code> table.
<code>scale_max</code>	The maximum value (in standard deviations) to show in the heatmap. Values larger than this are set to the max.
<code>scale_min</code>	The minimum value (in standard deviations) to show in the heatmap. Values smaller than this are set to the min.
<code>norm_method</code>	Determines how to transform expression values prior to rendering
<code>trend_formula</code>	A formula string specifying the model used in fitting the spline curve for each gene/feature.
<code>return_heatmap</code>	Whether to return the pheatmap object to the user.
<code>cores</code>	Number of cores to use when smoothing the expression curves shown in the heatmap.
<code>...</code>	Additional arguments passed to <code>buildBranchCellDataSet</code>

Value

A list of `heatmap_matrix` (expression matrix for the branch commitment), `ph` (pheatmap heatmap object), `annotation_row` (annotation dataframe for the row), `annotation_col` (annotation dataframe for the column).

```
plot_multiple_branches_heatmap2
```

Create a heatmap to demonstrate the bifurcation of gene expression along multiple branches

Description

Create a heatmap to demonstrate the bifurcation of gene expression along multiple branches

Usage

```
plot_multiple_branches_heatmap2(
  cds = NULL,
  branches,
  branches_name = NULL,
  cluster_rows = TRUE,
  hclust_method = "ward.D2",
  num_clusters = 6,
  hmcols = NULL,
  add_annotation_row = NULL,
  add_annotation_col = NULL,
  show_rownames = FALSE,
  use_gene_short_name = TRUE,
  norm_method = c("vstExprs", "log"),
  scale_max = 3,
  scale_min = -3,
  trend_formula = "~sm.ns(Pseudotime, df=3)",
  return_heatmap = FALSE,
  cores = 1
)
```

Arguments

<code>cds</code>	CellDataSet for the experiment (normally only the branching genes detected with BEAM)
<code>branches</code>	The terminal branches (states) on the developmental tree you want to investigate.
<code>branches_name</code>	Name (for example, cell type) of branches you believe the cells on the branches are associated with.
<code>cluster_rows</code>	Whether to cluster the rows of the heatmap.
<code>hclust_method</code>	The method used by pheatmap to perform hierarchical clustering of the rows.
<code>num_clusters</code>	Number of clusters for the heatmap of branch genes
<code>hmcols</code>	The color scheme for drawing the heatmap.
<code>add_annotation_row</code>	Additional annotations to show for each row in the heatmap. Must be a dataframe with one row for each row in the fData table of <code>cds_subset</code> , with matching IDs.

add_annotation_col	Additional annotations to show for each column in the heatmap. Must be a dataframe with one row for each cell in the pData table of cds_subset, with matching IDs.
show_rownames	Whether to show the names for each row in the table.
use_gene_short_name	Whether to use the short names for each row. If FALSE, uses row IDs from the fData table.
norm_method	Determines how to transform expression values prior to rendering
scale_max	The maximum value (in standard deviations) to show in the heatmap. Values larger than this are set to the max.
scale_min	The minimum value (in standard deviations) to show in the heatmap. Values smaller than this are set to the min.
trend_formula	A formula string specifying the model used in fitting the spline curve for each gene/feature.
return_heatmap	Whether to return the pheatmap object to the user.
cores	Number of cores to use when smoothing the expression curves shown in the heatmap.

Value

A list of heatmap_matrix (expression matrix for the branch commitment), ph (pheatmap heatmap object), annotation_row (annotation data.frame for the row), annotation_col (annotation data.frame for the column).

plot_pseudotime_heatmap2

Plots a pseudotime-ordered, row-centered heatmap which is slightly modified in monocle2

Description

The function plot_pseudotime_heatmap takes a CellDataSet object (usually containing a only subset of significant genes) and generates smooth expression curves much like plot_genes_in_pseudotime. Then, it clusters these genes and plots them using the pheatmap package. This allows you to visualize modules of genes that co-vary across pseudotime.

Usage

```
plot_pseudotime_heatmap2(
  cds_subset,
  cluster_rows = TRUE,
  hclust_method = "ward.D2",
  num_clusters = 6,
  hmcols = NULL,
```

```

    add_annotation_row = NULL,
    add_annotation_col = NULL,
    show_rownames = FALSE,
    use_gene_short_name = TRUE,
    norm_method = c("log", "vstExprs"),
    scale_max = 3,
    scale_min = -3,
    trend_formula = "~sm.ns(Pseudotime, df=3)",
    return_heatmap = FALSE,
    cores = 1
)

```

Arguments

<code>cds_subset</code>	CellDataSet for the experiment (normally only the branching genes detected with <code>branchTest</code>)
<code>cluster_rows</code>	Whether to cluster the rows of the heatmap.
<code>hclust_method</code>	The method used by pheatmap to perform hierarchical clustering of the rows.
<code>num_clusters</code>	Number of clusters for the heatmap of branch genes
<code>hmcols</code>	The color scheme for drawing the heatmap.
<code>add_annotation_row</code>	Additional annotations to show for each row in the heatmap. Must be a dataframe with one row for each row in the <code>fData</code> table of <code>cds_subset</code> , with matching IDs.
<code>add_annotation_col</code>	Additional annotations to show for each column in the heatmap. Must be a dataframe with one row for each cell in the <code>pData</code> table of <code>cds_subset</code> , with matching IDs.
<code>show_rownames</code>	Whether to show the names for each row in the table.
<code>use_gene_short_name</code>	Whether to use the short names for each row. If <code>FALSE</code> , uses row IDs from the <code>fData</code> table.
<code>norm_method</code>	Determines how to transform expression values prior to rendering
<code>scale_max</code>	The maximum value (in standard deviations) to show in the heatmap. Values larger than this are set to the max.
<code>scale_min</code>	The minimum value (in standard deviations) to show in the heatmap. Values smaller than this are set to the min.
<code>trend_formula</code>	A formula string specifying the model used in fitting the spline curve for each gene/feature.
<code>return_heatmap</code>	Whether to return the pheatmap object to the user.
<code>cores</code>	Number of cores to use when smoothing the expression curves shown in the heatmap.

Value

A list of heatmap_matrix (expression matrix for the branch commitment), ph (pheatmap heatmap object), annotation_row (annotation data.frame for the row), annotation_col (annotation data.frame for the column).

prepareDataFromscRNA *Prepare scRNA Data for clusterGvis Analysis*

Description

This function prepares single-cell RNA sequencing (scRNA-seq) data for differential gene expression analysis. It extracts the expression data for the specified cells and genes, and organizes them into a dataframe format suitable for downstream analysis.

Usage

```
prepareDataFromscRNA(
  object = NULL,
  diffData = NULL,
  showAverage = TRUE,
  cells = NULL,
  group.by = "ident",
  assays = "RNA",
  slot = "data",
  scale.data = TRUE,
  cluster.order = NULL,
  keep.uniqGene = TRUE,
  sep = "_"
)
```

Arguments

object	an object of class Seurat containing the scRNA-seq data.
diffData	a dataframe containing information about the differential expression analysis which can be output from function FindAllMarkers.
showAverage	a logical indicating whether to show the average gene expression across all cells.
cells	a vector of cell names to extract from the Seurat object. If NULL, all cells will be used.
group.by	a string specifying the grouping variable for differential expression analysis. Default is 'ident', which groups cells by their assigned clusters.
assays	a string or vector of strings specifying the assay(s) to extract from the Seurat object. Default is 'RNA'.
slot	a string specifying the slot name where the assay data is stored in the Seurat object. Default is 'data'.

scale.data	whether do Z-score for expression data, default TRUE.
cluster.order	the celltype orders.
keep.uniqGene	a logical indicating whether to keep only unique gene names. Default is TRUE.
sep	a character string to separate gene and cell names in the output dataframe. Default is "_".

Value

a dataframe containing the expression data for the specified genes and cells, organized in a format suitable for differential gene expression analysis.

```
pre_pseudotime_matrix
```

Calculate and return a smoothed pseudotime matrix for the given gene list

Description

This function takes in a monocle3 object and returns a smoothed pseudotime matrix for the given gene list, either in counts or normalized form. The function first matches the gene list with the rownames of the SummarizedExperiment object, and then orders the pseudotime information. The function then uses smooth.spline to apply smoothing to the data. Finally, the function normalizes the data by subtracting the mean and dividing by the standard deviation for each row.

Usage

```
pre_pseudotime_matrix(
  cds_obj = NULL,
  assays = c("counts", "normalized"),
  gene_list = NULL
)
```

Arguments

cds_obj	A monocle3 object
assays	Type of assay to be used for the analysis, either "counts" or "normalized"
gene_list	A vector of gene names

Value

A smoothed pseudotime matrix for the given gene list

pseudotime	<i>Generic to extract pseudotime from CDS object</i>
------------	--

Description

Generic to extract pseudotime from CDS object

Usage

```
pseudotime(x, reduction_method = "UMAP")
```

Arguments

x	A cell_data_set object.
reduction_method	Reduced dimension to extract pseudotime for.

Value

Pseudotime values.

Author(s)

<https://github.com/cole-trapnell-lab/monocle3>

pseudotime, cell_data_set-method	<i>Method to extract pseudotime from CDS object</i>
----------------------------------	---

Description

Method to extract pseudotime from CDS object

Usage

```
## S4 method for signature 'cell_data_set'  
pseudotime(x, reduction_method = "UMAP")
```

Arguments

x	A cell_data_set object.
reduction_method	Reduced dimension to extract clusters for.

Value

Pseudotime values.

`sig_gene_names`*This is a test data for this package test data description*

Description

This is a test data for this package test data description

Usage`sig_gene_names`**Format**

An object of class character of length 1331.

Author(s)

JunZhang

`size_factors`*Get the size factors from a cds object.*

Description

A wrapper around `colData(cds)$Size_Factor`

Usage`size_factors(cds)`**Arguments**

`cds` A `cell_data_set` object.

Value

An updated `cell_data_set` object

`termanno`*This is a test data for this package test data description*

Description

This is a test data for this package test data description

Usage

```
termanno
```

Format

An object of class `data.frame` with 24 rows and 2 columns.

Author(s)

Junjun Lao

`termanno2`*This is a test data for this package test data description*

Description

This is a test data for this package test data description

Usage

```
termanno2
```

Format

An object of class `data.frame` with 24 rows and 3 columns.

Author(s)

Junjun Lao

traverseTree	<i>traverseTree function</i>
--------------	------------------------------

Description

traverseTree function

Usage

```
traverseTree(g, starting_cell, end_cells)
```

Arguments

g	NULL
starting_cell	NULL
end_cells	NULL

visCluster	<i>using visCluster to visualize cluster results from clusterData and enrichCluster output</i>
------------	--

Description

Visualize Clustered Gene Data Using Line Plots and Heatmaps

Usage

```
visCluster(
  object = NULL,
  ht.col.list = list(col_range = c(-2, 0, 2), col_color = c("#08519C", "white",
    "#A50F15")),
  border = TRUE,
  plot.type = c("line", "heatmap", "both"),
  ms.col = c("#0099CC", "grey90", "#CC3333"),
  line.size = 0.1,
  line.col = "grey90",
  add.mline = TRUE,
  mline.size = 2,
  mline.col = "#CC3333",
  ncol = 4,
  ctAnno.col = NULL,
  set.md = "median",
  textbox.pos = c(0.5, 0.8),
  textbox.size = 8,
  panel.arg = c(2, 0.25, 4, "grey90", NA),
```

```
ggplot.panel.arg = c(2, 0.25, 4, "grey90", NA),
annoTerm.data = NULL,
annoTerm.mside = "right",
termAnno.arg = c("grey95", "grey50"),
add.bar = FALSE,
bar.width = 8,
textbar.pos = c(0.8, 0.8),
go.col = NULL,
go.size = NULL,
by.go = "anno_link",
annoKegg.data = NULL,
annoKegg.mside = "right",
keggAnno.arg = c("grey95", "grey50"),
add.kegg.bar = FALSE,
kegg.col = NULL,
kegg.size = NULL,
by.kegg = "anno_link",
word_wrap = TRUE,
add_new_line = TRUE,
add.box = FALSE,
boxcol = NULL,
box.arg = c(0.1, "grey50"),
add.point = FALSE,
point.arg = c(19, "orange", "orange", 1),
add.line = TRUE,
line.side = "right",
markGenes = NULL,
markGenes.side = "right",
genes.gp = c("italic", 10, NA),
term.text.limit = c(10, 18),
mulGroup = NULL,
lgd.label = NULL,
show_row_names = FALSE,
subgroup.anno = NULL,
annnoblock.text = TRUE,
annnoblock.gp = c("white", 8),
add.sampleanno = TRUE,
sample.group = NULL,
sample.col = NULL,
sample.order = NULL,
cluster.order = NULL,
sample.cell.order = NULL,
HeatmapAnnotation = NULL,
column.split = NULL,
cluster_columns = FALSE,
pseudotime_col = NULL,
gglist = NULL,
row_annotation_obj = NULL,
```

```
    ...
  )
```

Arguments

<code>object</code>	clusterData object, default NULL.
<code>ht.col.list</code>	list of heatmap <code>col_range</code> and <code>col_color</code> , default <code>list(col_range = c(-2, 0, 2), col_color = c("#08519C", "white", "#A50F15"))</code> .
<code>border</code>	whether add border for heatmap, default TRUE.
<code>plot.type</code>	the plot type to choose which including "line", "heatmap" and "both".
<code>ms.col</code>	membership line color from Mfuzz cluster method results, default <code>c('#0099CC', 'grey90', '#CC3333')</code> .
<code>line.size</code>	line size for line plot, default 0.1.
<code>line.col</code>	line color for line plot, default "grey90".
<code>add.mline</code>	whether add median line on plot, default TRUE.
<code>mline.size</code>	median line size, default 2.
<code>mline.col</code>	median line color, default "#CC3333".
<code>ncol</code>	the columns for facet plot with line plot, default 4.
<code>ctAnno.col</code>	the heatmap cluster annotation bar colors, default NULL.
<code>set.md</code>	the represent line method on heatmap-line plot(mean/median), default "median".
<code>textbox.pos</code>	the relative position of text in left-line plot, default <code>c(0.5, 0.8)</code> .
<code>textbox.size</code>	the text size of the text in left-line plot, default 8.
<code>panel.arg</code>	the settings for the left-line panel which are panel size, gap, width, fill and col, default <code>c(2, 0.25, 4, "grey90", NA)</code> .
<code>ggplot.panel.arg</code>	the settings for the ggplot2 object plot panel which are panel size, gap, width, fill and col, default <code>c(2, 0.25, 4, "grey90", NA)</code> .
<code>annoTerm.data</code>	the GO term annotation for the clusters, default NULL.
<code>annoTerm.mside</code>	the wider GO term annotation box side, default "right".
<code>termAnno.arg</code>	the settings for GO term panel annotations which are fill and col, default <code>c("grey95", "grey50")</code> .
<code>add.bar</code>	whether add bar plot for GO enrichment, default FALSE.
<code>bar.width</code>	the GO enrichment bar width, default 8.
<code>textbar.pos</code>	the barplot text relative position, default <code>c(0.8, 0.8)</code> .
<code>go.col</code>	the GO term text colors, default NULL.
<code>go.size</code>	the GO term text size(numeric or "pval"), default NULL.
<code>by.go</code>	the GO term text box style("anno_link" or "anno_block"), default "anno_link".
<code>annoKegg.data</code>	the KEGG term annotation for the clusters, default NULL.
<code>annoKegg.mside</code>	the wider KEGG term annotation box side, default "right".
<code>keggAnno.arg</code>	the settings for KEGG term panel annotations which are fill and col, default <code>c("grey95", "grey50")</code> .
<code>add.kegg.bar</code>	whether add bar plot for KEGG enrichment, default FALSE.

kegg.col	the KEGG term text colors, default NULL.
kegg.size	the KEGG term text size(numeric or "pval"), default NULL.
by.kegg	the KEGG term text box style("anno_link" or "anno_block"), default "anno_link".
word_wrap	whether wrap the text, default TRUE.
add_new_line	whether add new line when text is long, default TRUE.
add.box	whether add boxplot, default FALSE.
boxcol	the box fill colors, default NULL.
box.arg	this is related to boxplot width and border color, default c(0.1,"grey50").
add.point	whether add point, default FALSE.
point.arg	this is related to point shape,fill,color and size, default c(19,"orange","orange",1).
add.line	whether add line, default TRUE.
line.side	the line annotation side, default "right".
markGenes	the gene names to be added on plot, default NULL.
markGenes.side	the gene label side, default "right".
genes.gp	gene labels graphics settings, default c('italic',10,NA).
term.text.limit	the GO term text size limit, default c(10,18).
mulGroup	to draw multiple lines annotation, supply the groups numbers with vector, default NULL.
lgd.label	the lines annotation legend labels, default NULL.
show_row_names	whether to show row names, default FALSE.
subgroup.anno	the sub-cluster for annotation, supply sub-cluster id, default NULL.
annnoblock.text	whether add cluster numbers on right block annotation, default TRUE.
annnoblock.gp	right block annotation text color and size, default c("white",8).
add.sampleanno	whether add column annotation, default TRUE.
sample.group	the column sample groups, default NULL.
sample.col	column annotation colors, default NULL.
sample.order	the orders for column samples, default NULL.
cluster.order	the row cluster orders for user's own defination, default NULL.
sample.cell.order	the celltype order when input is scRNA data and "showAverage = FALSE" for prepareDataFromscRNA.
HeatmapAnnotation	the 'HeatmapAnnotation' object from 'ComplexHeatmap' when you have multiple annotations, default NULL.
column.split	how to split the columns when supply multiple column annotations, default NULL.
cluster_columns	whether cluster the columns, default FALSE.

`pseudotime_col` the branch color control for monocle input data.
`gglist` a list of ggplot object to annotate each cluster, default NULL.
`row_annotation_obj` Row annotation for heatmap, it is a `ComplexHeatmap::rowAnnotation()` object when "markGenes.side" or "line.side" is "right". Otherwise is a list of named vectors.
`...` othe aruguments passed by Heatmap fuction.

Details

This function visualizes clustered gene expression data as line plots, heatmaps, or a combination of both, using the `ComplexHeatmap` and `ggplot2` frameworks. Gene annotations, sample annotations, and additional features like custom color schemes and annotations for GO/KEGG terms are supported for visualization.

Value

a ggplot2 or Heatmap object.

Author(s)

JunZhang

Examples

```

data("exps")

# mfuzz
cm <- clusterData(obj = exps,
                  cluster.method = "kmeans",
                  cluster.num = 8)

# plot
visCluster(object = cm,
           plot.type = "line")

```

Index

- * **datasets**
 - BEAM_res, [2](#)
 - exps, [9](#)
 - net, [11](#)
 - sig_gene_names, [20](#)
 - termanno, [21](#)
 - termanno2, [21](#)
- BEAM_res, [2](#)
- cell_data_set, [3](#)
- cell_data_set-class (cell_data_set), [3](#)
- check_dependency, [3](#)
- clusterData, [4](#)
- enrichCluster, [6](#)
- exprs, [8](#)
- exprs, cell_data_set-method, [8](#)
- exps, [9](#)
- filter.std (filter.std modified by Mfuzz filter.std), [9](#)
- filter.std modified by Mfuzz filter.std, [9](#)
- getClusters, [10](#)
- net, [11](#)
- normalized_counts, [11](#)
- plot_genes_branched_heatmap2, [12](#)
- plot_multiple_branches_heatmap2, [14](#)
- plot_pseudotime_heatmap2, [15](#)
- pre_pseudotime_matrix, [18](#)
- prepareDataFromscRNA, [17](#)
- pseudotime, [19](#)
- pseudotime, cell_data_set-method, [19](#)
- sig_gene_names, [20](#)
- size_factors, [20](#)
- termanno, [21](#)
- termanno2, [21](#)
- traverseTree, [22](#)
- visCluster, [22](#)