

# The L<sup>A</sup>T<sub>E</sub>X metalogox package

v1.06 — 2024/03/07

© 2019, 2023–2024 Brian Dunn  
<https://github.com/bdtc/metalogox>

Automatically adjusts the T<sub>E</sub>X logo and related, depending on the font.

Font	Default	metalogox
Latin Modern	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Times	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Bookman	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Erewhon	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Libre Caslon	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Libertinus	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
IM Fell English	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Coelacanth	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Alegreya	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Helvetica	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X
Antiqua	L <sup>A</sup> T <sub>E</sub> X	L <sup>A</sup> T <sub>E</sub> X

## Abstract

The metalogox package extends the metalogo package to automatically adjust the appearance of the logos T<sub>E</sub>X, L<sup>A</sup>T<sub>E</sub>X, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X, and LuaL<sup>A</sup>T<sub>E</sub>X, depending on the font detected or the option given to metalogox.

Most of the serif and sans fonts listed at [The L<sup>A</sup>T<sub>E</sub>X Font Catalogue](#) are supported.

## Contents

<b>1 Introduction</b>	<b>3</b>
<b>2 Using the metalogo package</b>	<b>3</b>
<b>3 Code</b>	<b>5</b>
3.1 Required packages . . . . .	5
3.2 Package options . . . . .	5
3.2.1 Common synonyms . . . . .	15
3.2.2 Similar fonts . . . . .	16
3.3 Manual adjust selection . . . . .	17
3.4 Font detection . . . . .	17
3.5 Option declaration . . . . .	24
3.6 Default settings . . . . .	24
3.7 Option trigger . . . . .	25
3.8 Support for the hologo and hvlogos packages . . . . .	25
<b>A Change History</b>	<b>27</b>
<b>B Index</b>	<b>27</b>

## 1 Introduction

The rendering of the logos  $\TeX$ ,  $\LaTeX$ ,  $\LaTeX 2_{\epsilon}$ ,  $X\LaTeX$ ,  $X\TeX$ , and  $\Lua\TeX$  depends on the font, and in some cases the appearance of these logos may be improved with some minor adjustments of the positions of each of the elements. The metalogo package, by ANDREW GILBERT MOSCHOU, allows the user to specify these adjustments, but it is left to the user to determine the values to use. The correct value may depend on the font size, but in most cases predefined settings may be used.

The metalogo package assigns these settings for metalogo. The default is for LATIN MODERN and similar. If the font in use is supported by metalogo, settings for that font are automatically assigned, overriding the LATIN MODERN default. If the user specifies a package option, its settings override the default and also anything set by font detection.

The  $\LaTeX$  packages hologo and hvlogos are also supported when used with metalogo.

## 2 Using the metalogo package

`metalogo (Pkg)` In most cases, it is sufficient to simply load the metalogo package after the fonts have been selected:

```
\usepackage{<font packages>}
\setmainfont{Font Name}           (if using fontspec)
...etc ...
% \renewcommand{\familydefault}{\sfdefault} (optional)
...
\usepackage{metalogo}
```

Many fonts are supported by metalogo, and if one of these is in use then the appropriate settings are assigned automatically, according to the default text body font:  $\LaTeX 2_{\epsilon}$

**options** If several font packages are used, or a font is not recognized, it may be necessary to specify a metalogo package option, which overrides the font detection:

```
\usepackage[baskerville]{metalogo}
```

`\adjustlogos` {<package option>}

`\adjustlogos` may be used to adjust the logos for an unknown font. The mandatory argument is the same as the package options. This is a local change, and may be adjusted as needed.

```
\Fontskrivan (from the aurical package)
\adjustlogos{default} \LaTeXe  $\LaTeX 2_{\epsilon}$ 
\adjustlogos{baskerville} \LaTeXe  $\LaTeX 2_{\epsilon}$ 
```

`\autoadjustlogos` `\autoadjustlogos` may be used to make local changes according to the current font:

```
\textsf{Using \autoadjustlogos\LaTeXe}          Using LATEX 2ε
\textsf{Using \textrm{\autoadjustlogos\LaTeXe}} Using LATEX 2ε
```

`\autoadjustlogos*` The starred form, `\autoadjustlogos*`, is used by metalogo at the beginning of the document to set according to the default text body font.

### Notes:

- metalogo option names may be found in the following pages, or in the index.
  - metalogo options are always lowercase, even if a related package name may have uppercase letters.
  - Many options, such as `times`, are used to cover an entire category of related fonts.
  - Other options, such as `baskerville`, may be used for unrelated fonts which just happen to work well with the same logo settings.
  - For some fonts, X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X renders the reversed E in the X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X logo differently than pdfL<sup>A</sup>T<sub>E</sub>X and LuaL<sup>A</sup>T<sub>E</sub>X.
  - There are sometimes differences between the TYPE1 and the OTF/TTF fonts.
  - PDF display software may not render logos well on the screen at small display sizes. Zoom in to judge the quality of the logos.
  - The metalogo parameters were set according to the design preferences of the author of the metalogo package. Some may disagree with the design choices which were made, but the results are probably better than the defaults, and the user may take control using the metalogo package directly.
  - Since the same settings are usually shared by many fonts, some logos may not be perfect.
  - If a font is not known by metalogo then a warning is issued, and a few common options are recommended.
- [Unknown font?](#)
- Please contact the author of metalogo if an unknown font is found, especially if it is a common font, as sometimes the font family names are changed. See the contact link on the title page of this document.

## 3 Code

### 3.1 Required packages

```

1 \RequirePackage{metalogo}
2
3 \RequirePackage{xparse}
4
5 \RequirePackage{etoolbox}

```

### 3.2 Package options

Each of the following is a macro which is activated by passing the option of the same name to metalogo, or by calling `\adjustlogos`.

For example, either of the following sets the default metalogo logo adjustments:

```

\usepackage[default]{metalogo}
— or —
\adjustlogos{default}

```

`default` (*Opt*) The L<sup>A</sup>T<sub>E</sub>X and metalogo default settings.

```

6 \newcommand*{\MLX@default}{%
7   \setlogokern{Te}{-0.1667em}%
8   \setlogokern{eX}{-0.125em}%
9   \setlogokern{La}{-.36em}%
10  \setlogokern{aT}{-.15em}%
11  \setlogokern{Xe}{-.125em}%
12  \setlogokern{eT}{-.1667em}%
13  \setlogokern{eL}{-.125em}%
14  \setlogodrop{0.5ex}%
15 }

```

`accanthis` (*Opt*)

```

16 \newcommand*{\MLX@accanthis}{%
17   \setlogokern{Te}{-0.07em}%
18   \setlogokern{eX}{-0.05em}%
19   \setlogokern{La}{-.26em}%
20   \setlogokern{aT}{-.07em}%
21   \setlogokern{Xe}{-.06em}%
22   \setlogokern{eT}{-.05em}%
23   \setlogokern{eL}{-.06em}%
24   \setlogodrop{0.25ex}%
25 }

```

`alegreya` (*Opt*)

```

26 \newcommand*{\MLX@alegreya}{%
27   \setlogokern{Te}{-0.14em}%
28   \setlogokern{eX}{-0.12em}%

```

```
29 \setlogokern{La}{-.23em}%
30 \setlogokern{aT}{-.07em}%
31 \setlogokern{Xe}{-.06em}%
32 \setlogokern{eT}{-.10em}%
33 \setlogokern{eL}{-.12em}%
34 \setlogodrop{0.36ex}%
35 }
```

*algolrevived (Opt)*

```
36 \newcommand*\MLX@algolrevived}{%
37 \setlogokern{Te}{-0.17em}%
38 \setlogokern{eX}{-0.17em}%
39 \setlogokern{La}{-.40em}%
40 \setlogokern{aT}{-.06em}%
41 \setlogokern{Xe}{-.18em}%
42 \setlogokern{eT}{-.18em}%
43 \setlogokern{eL}{-.12em}%
44 \setlogodrop{0.28ex}%
45 }
```

*antpolt (Opt)*

```
46 \newcommand*\MLX@antpolt}{%
47 \setlogokern{Te}{-0.09em}%
48 \setlogokern{eX}{-0.08em}%
49 \setlogokern{La}{-.33em}%
50 \setlogokern{aT}{-.07em}%
51 \setlogokern{Xe}{-.07em}%
52 \setlogokern{eT}{-.10em}%
53 \setlogokern{eL}{-.06em}%
54 \setlogodrop{0.36ex}%
55 }
```

*avantgarde (Opt)*

```
56 \newcommand*\MLX@avantgarde}{%
57 \setlogokern{Te}{-0.10em}%
58 \setlogokern{eX}{-0.04em}%
59 \setlogokern{La}{-.26em}%
60 \setlogokern{aT}{-.10em}%
61 \setlogokern{Xe}{-.04em}%
62 \setlogokern{eT}{-.10em}%
63 \setlogokern{eL}{-.02em}%
64 \setlogodrop{0.40ex}%
65 }
```

*baskerville (Opt)*

```
66 \newcommand*\MLX@baskerville}{%
67 \setlogokern{Te}{-0.07em}%
68 \setlogokern{eX}{-0.05em}%
69 \setlogokern{La}{-.26em}%
```

```

70 \setlogokern{aT}{-.07em}%
71 \setlogokern{Xe}{-.06em}%
72 \setlogokern{eT}{-.07em}%
73 \setlogokern{eL}{-.06em}%
74 \setlogodrop{0.36ex}%
75 }

```

**berenis** (*Opt*)

```

76 \newcommand*{\MLX@berenis}{%
77 \setlogokern{Te}{-0.07em}%
78 \setlogokern{eX}{-0.05em}%
79 \setlogokern{La}{-.23em}%
80 \setlogokern{aT}{-.07em}%
81 \setlogokern{Xe}{-.06em}%
82 \setlogokern{eT}{-.10em}%
83 \setlogokern{eL}{-.02em}%
84 \setlogodrop{0.58ex}%
85 }

```

**bodoni** (*Opt*) Also see `librebodoni`.

```

86 \newcommand*{\MLX@bodoni}{%
87 \setlogokern{Te}{-0.11em}%
88 \setlogokern{eX}{-0.05em}%
89 \setlogokern{La}{-.26em}%
90 \setlogokern{aT}{-.07em}%
91 \setlogokern{Xe}{-.06em}%
92 \setlogokern{eT}{-.10em}%
93 \setlogokern{eL}{-.10em}%
94 \setlogodrop{0.37ex}%
95 }

```

**boisik** (*Opt*)

```

96 \newcommand*{\MLX@boisik}{%
97 \setlogokern{Te}{-0.09em}%
98 \setlogokern{eX}{-0.07em}%
99 \setlogokern{La}{-.35em}%
100 \setlogokern{aT}{-.07em}%
101 \setlogokern{Xe}{-.07em}%
102 \setlogokern{eT}{-.10em}%
103 \setlogokern{eL}{-.06em}%
104 \setlogodrop{0.55ex}%
105 }

```

**bookman** (*Opt*)

```

106 \newcommand*{\MLX@bookman}{%
107 \setlogokern{Te}{-0.03em}%
108 \setlogokern{eX}{-0.035em}%
109 \setlogokern{La}{-.25em}%
110 \setlogokern{aT}{-.00em}%

```

```
111 \setlogokern{Xe}{-.030em}%
112 \setlogokern{eT}{-.02em}%
113 \setlogokern{eL}{-.06em}%
114 \setlogodrop{0.36ex}%
115 }
```

*charter (Opt)*

```
116 \newcommand*\MLX@charter}{%
117 \setlogokern{Te}{-0.10em}%
118 \setlogokern{eX}{-0.07em}%
119 \setlogokern{La}{-.24em}%
120 \setlogokern{aT}{-.06em}%
121 \setlogokern{Xe}{-.07em}%
122 \setlogokern{eT}{-.10em}%
123 \setlogokern{eL}{-.06em}%
124 \setlogodrop{0.28ex}%
125 }
```

*crimson (Opt)*

```
126 \newcommand*\MLX@crimson}{%
127 \setlogokern{Te}{-0.05em}%
128 \setlogokern{eX}{-0.05em}%
129 \setlogokern{La}{-.23em}%
130 \setlogokern{aT}{-.07em}%
131 \setlogokern{Xe}{-.06em}%
132 \setlogokern{eT}{-.05em}%
133 \setlogokern{eL}{-.06em}%
134 \setlogodrop{0.36ex}%
135 }
```

*coelacanth (Opt)*

```
136 \newcommand*\MLX@coelacanth}{%
137 \setlogokern{Te}{-0.09em}%
138 \setlogokern{eX}{-0.05em}%
139 \setlogokern{La}{-.26em}%
140 \setlogokern{aT}{-.07em}%
141 \setlogokern{Xe}{-.06em}%
142 \setlogokern{eT}{-.10em}%
143 \setlogokern{eL}{-.06em}%
144 \setlogodrop{0.32ex}%
145 }
```

*didot (Opt)*

```
146 \newcommand*\MLX@didot}{%
147 \setlogokern{Te}{-0.11em}%
148 \setlogokern{eX}{-0.09em}%
149 \setlogokern{La}{-.34em}%
150 \setlogokern{aT}{-.11em}%
151 \setlogokern{Xe}{-.06em}%

```



```
152 \setlogokern{eT}{-.12em}%
153 \setlogokern{eL}{-.09em}%
154 \setlogodrop{0.44ex}%
155 }
```

#### droidserif (*Opt*)

```
156 \newcommand*\MLX@droidserif{%
157 \setlogokern{Te}{-0.11em}%
158 \setlogokern{eX}{-0.10em}%
159 \setlogokern{La}{-.30em}%
160 \setlogokern{aT}{-.08em}%
161 \setlogokern{Xe}{-.07em}%
162 \setlogokern{eT}{-.10em}%
163 \setlogokern{eL}{-.08em}%
164 \setlogodrop{0.30ex}%
165 }
```

#### droidsans (*Opt*)

```
166 \newcommand*\MLX@droidsans{%
167 \setlogokern{Te}{-0.11em}%
168 \setlogokern{eX}{-0.10em}%
169 \setlogokern{La}{-.24em}%
170 \setlogokern{aT}{-.08em}%
171 \setlogokern{Xe}{-.07em}%
172 \setlogokern{eT}{-.10em}%
173 \setlogokern{eL}{-.08em}%
174 \setlogodrop{0.30ex}%
175 }
```

#### gentium (*Opt*)

```
176 \newcommand*\MLX@gentium{%
177 \setlogokern{Te}{-0.07em}%
178 \setlogokern{eX}{-0.07em}%
179 \setlogokern{La}{-.26em}%
180 \setlogokern{aT}{-.07em}%
181 \setlogokern{Xe}{-.06em}%
182 \setlogokern{eT}{-.06em}%
183 \setlogokern{eL}{-.06em}%
184 \setlogodrop{0.24ex}%
185 }
```

#### helvetica (*Opt*)

```
186 \newcommand*\MLX@helvetica{%
187 \setlogokern{Te}{-0.15em}%
188 \setlogokern{eX}{-0.08em}%
189 \setlogokern{La}{-.26em}%
190 \setlogokern{aT}{-.08em}%
191 \setlogokern{Xe}{-.07em}%
192 \setlogokern{eT}{-.15em}%

```

```

193 \setlogokern{eL}{-.04em}%
194 \setlogodrop{0.40ex}%
195 }

```

*kerkis (Opt)*

```

196 \newcommand*\MLX@kerkis){%
197 \setlogokern{Te}{-0.02em}%
198 \setlogokern{eX}{-0.02em}%
199 \setlogokern{La}{-.25em}%
200 \setlogokern{aT}{-.00em}%
201 \setlogokern{Xe}{-.00em}%
202 \setlogokern{eT}{-.10em}%
203 \setlogokern{eL}{-.05em}%
204 \setlogodrop{0.38ex}%
205 }

```

*kpfonts (Opt)*

```

206 \newcommand*\MLX@kpfonts){%
207 \setlogokern{Te}{-0.11em}%
208 \setlogokern{eX}{-0.08em}%
209 \setlogokern{La}{-.30em}%
210 \setlogokern{aT}{-.11em}%
211 \setlogokern{Xe}{-.10em}%
212 \setlogokern{eT}{-.10em}%
213 \setlogokern{eL}{-.06em}%
214 \setlogodrop{0.33ex}%
215 }

```

*libertine (Opt)* Also see *libertinus*, below.

```

216 \newcommand*\MLX@libertine){%
217 \setlogokern{Te}{-0.05em}%
218 \setlogokern{eX}{-0.06em}%
219 \setlogokern{La}{-.25em}%
220 \setlogokern{aT}{-.05em}%
221 \setlogokern{Xe}{-.05em}%
222 \setlogokern{eT}{-.05em}%
223 \setlogokern{eL}{-.02em}%
224 \setlogodrop{0.32ex}%
225 }

```

*libertinus (Opt)* There is a difference in the raised ‘A’ vs. *libertine*.

```

226 \newcommand*\MLX@libertinus){%
227 \setlogokern{Te}{-0.05em}%
228 \setlogokern{eX}{-0.06em}%
229 \setlogokern{La}{-.28em}%
230 \setlogokern{aT}{-.05em}%
231 \setlogokern{Xe}{-.05em}%
232 \setlogokern{eT}{-.05em}%
233 \setlogokern{eL}{-.02em}%

```

```

234 \setlogodrop{0.32ex}%
235 }

```

`librebodoni` (*Opt*) Specific to LibreBodoni only.

```

236 \newcommand*{\MLX@librebodoni}{%
237 \setlogokern{Te}{-0.07em}%
238 \setlogokern{eX}{-0.05em}%
239 \setlogokern{La}{-.26em}%
240 \setlogokern{aT}{-.07em}%
241 \setlogokern{Xe}{-.06em}%
242 \setlogokern{eT}{-.10em}%
243 \setlogokern{eL}{-.02em}%
244 \setlogodrop{0.49ex}%
245 }

```

`lmodern` (*Opt*)

```

246 \newcommand*{\MLX@lmodern}{%
247 \setlogokern{Te}{-0.10em}%
248 \setlogokern{eX}{-0.06em}%
249 \setlogokern{La}{-.33em}%
250 \setlogokern{aT}{-.15em}%
251 \setlogokern{Xe}{-.07em}%
252 \setlogokern{eT}{-.10em}%
253 \setlogokern{eL}{-.08em}%
254 \setlogodrop{0.52ex}%
255 }

```

`lmodernsans` (*Opt*)

```

256 \newcommand*{\MLX@lmodernsans}{%
257 \setlogokern{Te}{-0.20em}%
258 \setlogokern{eX}{-0.06em}%
259 \setlogokern{La}{-.29em}%
260 \setlogokern{aT}{-.12em}%
261 \setlogokern{Xe}{-.07em}%
262 \setlogokern{eT}{-.20em}%
263 \setlogokern{eL}{-.08em}%
264 \setlogodrop{0.45ex}%
265 }

```

`merriweather` (*Opt*)

```

266 \newcommand*{\MLX@merriweather}{%
267 \setlogokern{Te}{-0.09em}%
268 \setlogokern{eX}{-0.09em}%
269 \setlogokern{La}{-.26em}%
270 \setlogokern{aT}{-.07em}%
271 \setlogokern{Xe}{-.06em}%
272 \setlogokern{eT}{-.10em}%
273 \setlogokern{eL}{-.06em}%
274 \setlogodrop{0.32ex}%

```

275 }

*newcent (Opt)*

```
276 \newcommand*{\MLX@newcent}{%
277   \setlogokern{Te}{-0.08em}%
278   \setlogokern{eX}{-0.09em}%
279   \setlogokern{La}{-.30em}%
280   \setlogokern{aT}{-.07em}%
281   \setlogokern{Xe}{-.07em}%
282   \setlogokern{eT}{-.10em}%
283   \setlogokern{eL}{-.06em}%
284   \setlogodrop{0.49ex}%
285 }
```

*noto (Opt)*

```
286 \newcommand*{\MLX@noto}{%
287   \setlogokern{Te}{-0.11em}%
288   \setlogokern{eX}{-0.10em}%
289   \setlogokern{La}{-.30em}%
290   \setlogokern{aT}{-.07em}%
291   \setlogokern{Xe}{-.10em}%
292   \setlogokern{eT}{-.10em}%
293   \setlogokern{eL}{-.06em}%
294   \setlogodrop{0.26ex}%
295 }
```

*palatino (Opt)*

```
296 \newcommand*{\MLX@palatino}{%
297   \setlogokern{Te}{-0.07em}%
298   \setlogokern{eX}{-0.09em}%
299   \setlogokern{La}{-.33em}%
300   \setlogokern{aT}{-.10em}%
301   \setlogokern{Xe}{-.09em}%
302   \setlogokern{eT}{-.08em}%
303   \setlogokern{eL}{-.07em}%
304   \setlogodrop{0.35ex}%
305 }
```

*pandora (Opt)*

```
306 \newcommand*{\MLX@pandora}{%
307   \setlogokern{Te}{-0.09em}%
308   \setlogokern{eX}{-0.08em}%
309   \setlogokern{La}{-.32em}%
310   \setlogokern{aT}{-.07em}%
311   \setlogokern{Xe}{-.08em}%
312   \setlogokern{eT}{-.10em}%
313   \setlogokern{eL}{-.06em}%
314   \setlogodrop{0.53ex}%
315 }
```

*paratype (Opt)*

```

316 \newcommand*{\MLX@paratype}{%
317   \setlogokern{Te}{-0.07em}%
318   \setlogokern{eX}{-0.10em}%
319   \setlogokern{La}{-.26em}%
320   \setlogokern{aT}{-.07em}%
321   \setlogokern{Xe}{-.06em}%
322   \setlogokern{eT}{-.10em}%
323   \setlogokern{eL}{-.06em}%
324   \setlogodrop{0.34ex}%
325 }

```

*plexserif (Opt)*

```

326 \newcommand*{\MLX@plexserif}{%
327   \setlogokern{Te}{-0.1667em}%
328   \setlogokern{eX}{-0.125em}%
329   \setlogokern{La}{-.30em}%
330   \setlogokern{aT}{-.10em}%
331   \setlogokern{Xe}{-.125em}%
332   \setlogokern{eT}{-.16em}%
333   \setlogokern{eL}{-.10em}%
334   \setlogodrop{0.5ex}%
335 }

```

*plexsans (Opt)*

```

336 \newcommand*{\MLX@plexsans}{%
337   \setlogokern{Te}{-0.1667em}%
338   \setlogokern{eX}{-0.10em}%
339   \setlogokern{La}{-.25em}%
340   \setlogokern{aT}{-.10em}%
341   \setlogokern{Xe}{-.10em}%
342   \setlogokern{eT}{-.17em}%
343   \setlogokern{eL}{-.10em}%
344   \setlogodrop{0.5ex}%
345 }

```

*quattrocento (Opt)* Compromises must be made here. It appears that the height of 1ex is incorrect for serif with X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X, Lua<sup>A</sup>T<sub>E</sub>X.

```

346 \newcommand*{\MLX@quattrocento}{%
347   \setlogokern{Te}{-0.09em}%
348   \setlogokern{eX}{-0.05em}%
349   \setlogokern{La}{-.26em}%
350   \setlogokern{aT}{-.07em}%
351   \setlogokern{Xe}{-.06em}%
352   \setlogokern{eT}{-.10em}%
353   \setlogokern{eL}{-.06em}%
354   \setlogodrop{.4ex}%
355 }

```

*sourceserifpro (Opt)*

```
356 \newcommand*{\MLX@sourceserifpro}{%
357   \setlogokern{Te}{-0.12em}%
358   \setlogokern{eX}{-0.09em}%
359   \setlogokern{La}{-.29em}%
360   \setlogokern{aT}{-.07em}%
361   \setlogokern{Xe}{-.09em}%
362   \setlogokern{eT}{-.10em}%
363   \setlogokern{eL}{-.09em}%
364   \setlogodrop{0.30ex}%
365 }
```

*sourcesanspro (Opt)*

```
366 \newcommand*{\MLX@sourcesanspro}{%
367   \setlogokern{Te}{-0.12em}%
368   \setlogokern{eX}{-0.09em}%
369   \setlogokern{La}{-.22em}%
370   \setlogokern{aT}{-.07em}%
371   \setlogokern{Xe}{-.09em}%
372   \setlogokern{eT}{-.10em}%
373   \setlogokern{eL}{-.09em}%
374   \setlogodrop{0.30ex}%
375 }
```

*times (Opt)*

```
376 \newcommand*{\MLX@times}{%
377   \setlogokern{Te}{-0.06em}%
378   \setlogokern{eX}{-0.05em}%
379   \setlogokern{La}{-.28em}%
380   \setlogokern{aT}{-.07em}%
381   \setlogokern{Xe}{-.06em}%
382   \setlogokern{eT}{-.06em}%
383   \setlogokern{eL}{-.02em}%
384   \setlogodrop{0.34ex}%
385 }
```

*utopia (Opt)*

```
386 \newcommand*{\MLX@utopia}{%
387   \setlogokern{Te}{-.08em}%
388   \setlogokern{eX}{-0.04em}%
389   \setlogokern{La}{-.21em}%
390   \setlogokern{aT}{-.10em}%
391   \setlogokern{Xe}{-.02em}%
392   \setlogokern{eT}{-.10em}%
393   \setlogokern{eL}{-.06em}%
394   \setlogodrop{0.30ex}%
395 }
```

*venturis (Opt)*

```

396 \newcommand*{\MLX@venturis}{%
397   \setlogokern{Te}{-0.07em}%
398   \setlogokern{eX}{-0.05em}%
399   \setlogokern{La}{-.22em}%
400   \setlogokern{aT}{-.07em}%
401   \setlogokern{Xe}{-.06em}%
402   \setlogokern{eT}{-.06em}%
403   \setlogokern{eL}{-.06em}%
404   \setlogodrop{0.36ex}%
405 }

```

*vera (Opt)*

```

406 \newcommand*{\MLX@vera}{%
407   \setlogokern{Te}{-0.12em}%
408   \setlogokern{eX}{-0.14em}%
409   \setlogokern{La}{-.32em}%
410   \setlogokern{aT}{-.05em}%
411   \setlogokern{Xe}{-.14em}%
412   \setlogokern{eT}{-.10em}%
413   \setlogokern{eL}{-.10em}%
414   \setlogodrop{0.235ex}%
415 }

```

*verasans (Opt)*

```

416 \newcommand*{\MLX@verasans}{%
417   \setlogokern{Te}{-0.12em}%
418   \setlogokern{eX}{-0.10em}%
419   \setlogokern{La}{-.28em}%
420   \setlogokern{aT}{-.05em}%
421   \setlogokern{Xe}{-.10em}%
422   \setlogokern{eT}{-.10em}%
423   \setlogokern{eL}{-.10em}%
424   \setlogodrop{0.35ex}%
425 }

```

### 3.2.1 Common synonyms

Synonyms for commonly-used fonts.

*tgbonum (Opt)*

```
426 \newcommand*{\MLX@tgbonum}{\MLX@bookman}
```

*tgheros (Opt)*

```
427 \newcommand*{\MLX@tgheros}{\MLX@helvetica}
```

*tgpagella (Opt)*

```
428 \newcommand*{\MLX@tgpagella}{\MLX@palatino}
```

tgschola (*Opt*)

```
429 \newcommand*{\MLX@tgschola}{\MLX@newcent}
```

tgtermes (*Opt*)

```
430 \newcommand*{\MLX@tgtermes}{\MLX@times}
```

### 3.2.2 Similar fonts

The following work well enough that a separate definition is probably not necessary.

antiqua (*Opt*)

```
431 \newcommand*{\MLX@antiqua}{\MLX@baskerville}
```

anttor (*Opt*)

```
432 \newcommand*{\MLX@anttor}{\MLX@antpolz}
```

artemisia (*Opt*)

```
433 \newcommand*{\MLX@artemisia}{\MLX@baskerville}
```

caladea (*Opt*)

```
434 \newcommand*{\MLX@caladea}{\MLX@baskerville}
```

caslon (*Opt*)

```
435 \newcommand*{\MLX@caslon}{\MLX@baskerville}
```

cochineal (*Opt*)

```
436 \newcommand*{\MLX@cochineal}{\MLX@baskerville}
```

concmath (*Opt*)

```
437 \newcommand*{\MLX@concmath}{\MLX@lmodern}
```

drm (*Opt*)

```
438 \newcommand*{\MLX@drm}{\MLX@lmodern}
```

garamond (*Opt*)

```
439 \newcommand*{\MLX@garamond}{\MLX@baskerville}
```

imfenglish (*Opt*)

```
440 \newcommand*{\MLX@imfenglish}{\MLX@baskerville}
```



`literat` (*Opt*)

```
441 \newcommand*\MLX@literat\MLX@baskerville}
```

`roboto` (*Opt*)

```
442 \newcommand*\MLX@roboto\MLX@pandora}
```

`romande` (*Opt*)

```
443 \newcommand*\MLX@romande\MLX@baskerville}
```

### 3.3 Manual adjust selection

`\adjustlogos` {*<package option>*}

If the given option matches a predefined `\MLX@...` macro, use it.

```
444 \newcommand*\adjustlogos[1]{%
445   \ifcsdef\MLX@#1{%
446     \PackageInfo{metalogoX}{Setting #1}%
447     \csuse\MLX@#1}%
448   }{%
449     \PackageError{metalogoX}{Unknown setting #1}%
450     {See the metalogoX documentation for a list of options.}%
451   }%
452 }
```

### 3.4 Font detection

`MLX@@foundfont` (*bool*) Found the font?

```
453 \newbool\MLX@@foundfont}
```

`\MLX@@detectvariant` {*<1: family>*} {*<2: variant>*} {*<3: name>*} {*<4: setting>*}

If the font variant matches, adjust accordingly.

(The doubled @ is to distinguish this from a valid metalogoX option.)

```
454 \newcommand*\MLX@@detectvariant[4]{%
455 \ifdefstring\MLX@@thisfont\#1#2}{%
456   \booltrue\MLX@@foundfont}%
457   \PackageInfo{metalogoX}{Detected #1#2, #3. Using #4}%
458   \adjustlogos\#4}%
459 }{ }%
460 }
```

`\MLX@@detectone {<1: family>} {<2: name>} {<3: setting>}`

Tests variants. If a font family and variant matches, select the metalogox option.

(The doubled @ is to distinguish this from a valid metalogox option.)

```
461 \NewDocumentCommand{\MLX@@detectone}{m m m}{%
462 \MLX@@detectvariant{#1}{-}{#2}{#3}%
463 \MLX@@detectvariant{#1}{-TLF}{#2}{#3}%
464 \MLX@@detectvariant{#1}{-LF}{#2}{#3}%
465 \MLX@@detectvariant{#1}{-OsF}{#2}{#3}%
466 \MLX@@detectvariant{#1}{-TosF}{#2}{#3}%
467 \MLX@@detectvariant{#1}{Condensed-TLF}{#2}{#3}%
468 \MLX@@detectvariant{#1}{Condensed-LF}{#2}{#3}%
469 \MLX@@detectvariant{#1}{Condensed-OsF}{#2}{#3}%
470 \MLX@@detectvariant{#1}{Condensed-TosF}{#2}{#3}%
471 \MLX@@detectvariant{#1}{(0)}{#2}{#3}%
472 \MLX@@detectvariant{#1}{(1)}{#2}{#3}%
473 }
```

`\autoadjustlogos *`

Search a list of fonts and variants, looking for a match with the current one.

```
474 \NewDocumentCommand{\autoadjustlogos}{s}{%
```

Not yet discovered the font:

```
475 \boolfalse{MLX@@foundfont}%
```

If starred, use the text body font, else use the local font:

```
476 \IfBooleanTF{#1}{%
477   \edef\MLX@@thisfont{\familydefault}%
478 }{%
479   \edef\MLX@@thisfont{\f@family}%
480 }%
```

Announce the desired font:

```
481 \PackageInfo{metalogox}{Searching for \MLX@@thisfont}%
```

Default if nothing is found:

```
482 \adjustlogos{lmodern}%
```

Search a list of possibilities:

```
483 \MLX@@detectone{AccanthisADFStdNoThree}{accanthis}{accanthis}%
484 \MLX@@detectone{AccanthisADFStdNo3}{accanthis}{accanthis}%
485 \MLX@@detectone{Alegreya}{Alegreya}{alegreya}%
486 \MLX@@detectone{AlegreyaSans}{AlegreyaSans}{alegreya}%
```

487 \MLX@@detectone{AlgolRevived}{algolrevived}{algolrevived}%  
488 \MLX@@detectone{uaq}{antiqua}{baskerville}%  
489 \MLX@@detectone{antp}{antpolt}{antpolt}%  
490 \MLX@@detectone{AntykwaPoltawskiego}{antpolt}{antpolt}%  
491 \MLX@@detectone{antt}{anttor}{antpolt}%  
492 \MLX@@detectone{AntykwaTorunska}{anttor}{antpolt}%  
493 \MLX@@detectone{ArchivZero}{Archiv0}{helvetica}%  
494 \MLX@@detectone{Archiv0}{Archiv0}{helvetica}%  
495 \MLX@@detectone{fav}{arev}{vera}%  
496 \MLX@@detectone{Arimo}{Arimo}{helvetica}%  
497 \MLX@@detectone{atkinsn}{Atkinson Hyperlegible}{helvetica}%  
498 \MLX@@detectone{AtkinsonHyperlegible}{Atkinson Hyperlegible}{helvetica}%  
499 \MLX@@detectone{pag}{Avant Garde}{avantgarde}%  
500 \MLX@@detectone{qag}{tgadventor}{avantgarde}%  
501 \MLX@@detectone{ybv}{baskervald}{baskerville}%  
502 \MLX@@detectone{ybv}{baskervald}{baskerville}%  
503 \MLX@@detectone{Baskervaldx}{Baskervaldx}{baskerville}%  
504 \MLX@@detectone{BaskervilleF}{baskervillef}{baskerville}%  
505 \MLX@@detectone{fve}{beraserif}{vera}%  
506 \MLX@@detectone{fvs}{berasans}{verasans}%  
507 \MLX@@detectone{ybd}{berenis}{berenis}%  
508 \MLX@@detectone{ybd2}{berenis}{berenis}%  
509 \MLX@@detectone{ybd2j}{berenis}{berenis}%  
510 \MLX@@detectone{ybdj}{berenis}{berenis}%  
511 \MLX@@detectone{BerenisADFPPro}{berenis}{berenis}%  
512 \MLX@@detectone{LinuxBiolinumT}{biolinum}{helvetica}%  
513 \MLX@@detectone{Cabin}{Cabin}{helvetica}%  
514 \MLX@@detectone{CabinCondensed}{CabinCondensed}{helvetica}%  
515 \MLX@@detectone{Caladea}{caladea}{baskerville}%  
516 \MLX@@detectone{cantarell}{cantarell}{helvetica}%  
517 \MLX@@detectone{Crlt}{Carlito}{crimson}%  
518 \MLX@@detectone{Carlito}{Carlito}{crimson}%  
519 \MLX@@detectone{charssil}{CharisSIL}{times}%  
520 \MLX@@detectone{CharisSIL}{CharisSIL}{times}%  
521 \MLX@@detectone{mdbch}{mdbch - Math Design Bitstream Charter}{charter}%  
522 \MLX@@detectone{Chivo}{Chivo}{helvetica}%  
523 \MLX@@detectone{ClearSans}{Clear Sans}{helvetica}%  
524 \MLX@@detectone{Cochineal}{cochineal}{baskerville}%  
525 \MLX@@detectone{Coelacanth}{coelacanth}{coelacanth}%  
526 \MLX@@detectone{comfortaa}{comfortaa}{avantgarde}%  
527 \MLX@@detectone{ComicNeue}{comicneue}{avantgarde}%  
528 \MLX@@detectone{cmbr}{Computer Modern Bright}{lmodern}%  
529 \MLX@@detectone{lcmss}{Computer Modern Sans Quote}{lmodern}%  
530 \MLX@@detectone{cmr}{Computer Modern Roman}{lmodern}%  
531 \MLX@@detectone{cmss}{Computer Modern Sans}{lmodernsans}%  
532 \MLX@@detectone{ccr}{concmath}{lmodern}%  
533 \MLX@@detectone{CormorantGaramond}{CormorantGaramond}{garamond}%  
534 \MLX@@detectone{Crimson}{crimson}{crimson}%  
535 \MLX@@detectone{CrimsonPro}{CrimsonPro}{crimson}%  
536 \MLX@@detectone{cpr}{Cuprum}{utopia}%  
537 \MLX@@detectone{Cuprum}{Cuprum}{utopia}%  
538 \MLX@@detectone{cyklop}{Cyklop}{lmodern}%  
539 \MLX@@detectone{DejaVuSerif}{DejaVuSerif}{vera}%  
540 \MLX@@detectone{DejaVuSerifCondensed}{DejaVuSerif Condensed}{vera}%

541 \MLX@@detectone{DejaVuSans}{DejaVuSans}{verasans}%  
542 \MLX@@detectone{drm}{DRM}{lmodern}%  
543 \MLX@@detectone{droidserif}{Droid Serif}{droidserif}%  
544 \MLX@@detectone{droidsans}{Droid Sans}{droidsans}%  
545 \MLX@@detectone{DroidSerif}{Droid Serif}{droidserif}%  
546 \MLX@@detectone{DroidSans}{Droid Sans}{droidsans}%  
547 \MLX@@detectone{EBGaramond}{EB Garamond}{garamond}%  
548 \MLX@@detectone{EBGaramond12}{EB Garamond}{garamond}%  
549 \MLX@@detectone{Eczar}{Eczar}{times}%  
550 \MLX@@detectone{erewhon}{erewhon}{utopia}%  
551 \MLX@@detectone{Erewhon}{erewhon}{utopia}%  
552 \MLX@@detectone{fbb}{fbb}{baskerville}%  
553 \MLX@@detectone{FiraSans}{Fira Sans}{helvetica}%  
554 \MLX@@detectone{FiraSansBook}{Fira Sans}{helvetica}%  
555 \MLX@@detectone{FiraSansThin}{Fira Sans}{helvetica}%  
556 \MLX@@detectone{FiraSansLight}{Fira Sans}{helvetica}%  
557 \MLX@@detectone{FiraSansExtraLight}{Fira Sans}{helvetica}%  
558 \MLX@@detectone{FiraSansUltraLight}{Fira Sans}{helvetica}%  
559 \MLX@@detectone{futs}{fourier}{utopia}%  
560 \MLX@@detectone{fnc}{fouriernc}{newcent}%  
561 \MLX@@detectone{gentium}{gentium}{gentium}%  
562 \MLX@@detectone{GentiumPlus}{gentium}{gentium}%  
563 \MLX@@detectone{artemisia}{gfsartemisia}{baskerville}%  
564 \MLX@@detectone{GFSArtemisia}{gfsartemisia}{baskerville}%  
565 \MLX@@detectone{artemisiaeuler}{gfsartemisia}{baskerville}%  
566 \MLX@@detectone{bodoni}{gfsbodoni}{bodoni}%  
567 \MLX@@detectone{GFSBodoni}{gfsbodoni}{bodoni}%  
568 \MLX@@detectone{udidot}{gfsdidot}{didot}%  
569 \MLX@@detectone{FreeSerif}{GNU Freeserif}{times}%  
570 \MLX@@detectone{FreeSans}{GNU Freesans}{helvetica}%  
571 \MLX@@detectone{neohellenic}{GFS Neohellenic}{helvetica}%  
572 \MLX@@detectone{GFSNeohellenic}{GFS Neohellenic}{helvetica}%  
573 \MLX@@detectone{Gillius}{Gillius}{avantgarde}%  
574 \MLX@@detectone{GilliusADF}{Gillius}{avantgarde}%  
575 \MLX@@detectone{GilliusADFCond}{Gillius}{avantgarde}%  
576 \MLX@@detectone{GilliusADFNo2}{Gillius}{avantgarde}%  
577 \MLX@@detectone{GilliusADFNo2Cond}{Gillius}{avantgarde}%  
578 \MLX@@detectone{Go}{Go Sans}{helvetica}%  
579 \MLX@@detectone{phv}{helvet}{helvetica}%  
580 \MLX@@detectone{Heuristica}{heuristica}{utopia}%  
581 \MLX@@detectone{heuristica}{heuristica}{utopia}%  
582 \MLX@@detectone{IbarraRealNova}{Ibarra}{times}%  
583 \MLX@@detectone{IMFELLEnglish}{imfellEnglish}{baskerville}%  
584 \MLX@@detectone{InriaSans}{Inria Sans}{helvetica}%  
585 \MLX@@detectone{InriaSerif}{Inria Serif}{baskerville}%  
586 \MLX@@detectone{Inter}{Inter}{helvetica}%  
587 \MLX@@detectone{iwona}{Iwona}{helvetica}%  
588 \MLX@@detectone{Iwona}{Iwona}{helvetica}%  
589 \MLX@@detectone{IwonaLight}{Iwona}{helvetica}%  
590 \MLX@@detectone{IwonaMedium}{Iwona}{helvetica}%  
591 \MLX@@detectone{IwonaHeavy}{Iwona}{helvetica}%  
592 \MLX@@detectone{IwonaCond}{Iwona}{helvetica}%  
593 \MLX@@detectone{IwonaCondLight}{Iwona}{helvetica}%  
594 \MLX@@detectone{IwonaCondMedium}{Iwona}{helvetica}%

595 \MLX@@detectone{IwonaCondHeavy}{Iwona}{helvetica}%  
596 \MLX@@detectone{Junicode}{Junicode}{times}%  
597 \MLX@@detectone{mak}{kerkis}{kerkis}%  
598 \MLX@@detectone{maksf}{kerkis sans}{kerkis}%  
599 \MLX@@detectone{jkp}{kpfonts}{kpfonts}%  
600 \MLX@@detectone{jkpf}{kpfonts}{kpfonts}%  
601 \MLX@@detectone{jkpfosn}{kpfonts}{kpfonts}%  
602 \MLX@@detectone{jkpk}{kpfonts}{kpfonts}%  
603 \MLX@@detectone{jkpkf}{kpfonts}{kpfonts}%  
604 \MLX@@detectone{jkpkfosn}{kpfonts}{kpfonts}%  
605 \MLX@@detectone{jkpkos}{kpfonts}{kpfonts}%  
606 \MLX@@detectone{jkpkosn}{kpfonts}{kpfonts}%  
607 \MLX@@detectone{jkpkvos}{kpfonts}{kpfonts}%  
608 \MLX@@detectone{jkpl}{kpfonts}{kpfonts}%  
609 \MLX@@detectone{jkplf}{kpfonts}{kpfonts}%  
610 \MLX@@detectone{jkplfosn}{kpfonts}{kpfonts}%  
611 \MLX@@detectone{jkplk}{kpfonts}{kpfonts}%  
612 \MLX@@detectone{jkplkf}{kpfonts}{kpfonts}%  
613 \MLX@@detectone{jkplkfosn}{kpfonts}{kpfonts}%  
614 \MLX@@detectone{jkplkos}{kpfonts}{kpfonts}%  
615 \MLX@@detectone{jkplkosn}{kpfonts}{kpfonts}%  
616 \MLX@@detectone{jkplkvos}{kpfonts}{kpfonts}%  
617 \MLX@@detectone{jkplos}{kpfonts}{kpfonts}%  
618 \MLX@@detectone{jkplosn}{kpfonts}{kpfonts}%  
619 \MLX@@detectone{jkplvos}{kpfonts}{kpfonts}%  
620 \MLX@@detectone{jkpos}{kpfonts}{kpfonts}%  
621 \MLX@@detectone{jkposn}{kpfonts}{kpfonts}%  
622 \MLX@@detectone{jkpss}{kpfonts}{kpfonts}%  
623 \MLX@@detectone{jkpssf}{kpfonts}{kpfonts}%  
624 \MLX@@detectone{jkpssfosn}{kpfonts}{kpfonts}%  
625 \MLX@@detectone{jkpssk}{kpfonts}{kpfonts}%  
626 \MLX@@detectone{jkpsskf}{kpfonts}{kpfonts}%  
627 \MLX@@detectone{jkpsskfosn}{kpfonts}{kpfonts}%  
628 \MLX@@detectone{jkpsskos}{kpfonts}{kpfonts}%  
629 \MLX@@detectone{jkpsskosn}{kpfonts}{kpfonts}%  
630 \MLX@@detectone{jkpsskvos}{kpfonts}{kpfonts}%  
631 \MLX@@detectone{jkpssos}{kpfonts}{kpfonts}%  
632 \MLX@@detectone{jkpssosn}{kpfonts}{kpfonts}%  
633 \MLX@@detectone{jkpssvos}{kpfonts}{kpfonts}%  
634 \MLX@@detectone{jkptt}{kpfonts}{kpfonts}%  
635 \MLX@@detectone{jkpttos}{kpfonts}{kpfonts}%  
636 \MLX@@detectone{jkpttosn}{kpfonts}{kpfonts}%  
637 \MLX@@detectone{jkpttvos}{kpfonts}{kpfonts}%  
638 \MLX@@detectone{jkpvos}{kpfonts}{kpfonts}%  
639 \MLX@@detectone{jkpx}{kpfonts}{kpfonts}%  
640 \MLX@@detectone{jkpxf}{kpfonts}{kpfonts}%  
641 \MLX@@detectone{jkpxfosn}{kpfonts}{kpfonts}%  
642 \MLX@@detectone{jkpxk}{kpfonts}{kpfonts}%  
643 \MLX@@detectone{jkpxkf}{kpfonts}{kpfonts}%  
644 \MLX@@detectone{jkpxkfosn}{kpfonts}{kpfonts}%  
645 \MLX@@detectone{jkpxkos}{kpfonts}{kpfonts}%  
646 \MLX@@detectone{jkpxkosn}{kpfonts}{kpfonts}%  
647 \MLX@@detectone{jkpxkvos}{kpfonts}{kpfonts}%  
648 \MLX@@detectone{jkpxos}{kpfonts}{kpfonts}%

649 \MLX@@detectone{jkpxosn}{kpfonts}{kpfonts}%  
650 \MLX@@detectone{jkpxvos}{kpfonts}{kpfonts}%  
651 \MLX@@detectone{JosefinSans}{Josefin}{lmodern}%  
652 \MLX@@detectone{kurier}{Kurier}{helvetica}%  
653 \MLX@@detectone{Kurier}{Kurier}{helvetica}%  
654 \MLX@@detectone{KurierLight}{Kurier}{helvetica}%  
655 \MLX@@detectone{KurierMedium}{Kurier}{helvetica}%  
656 \MLX@@detectone{KurierHeavy}{Kurier}{helvetica}%  
657 \MLX@@detectone{KurierCond}{Kurier}{helvetica}%  
658 \MLX@@detectone{KurierCondLight}{Kurier}{helvetica}%  
659 \MLX@@detectone{KurierCondMedium}{Kurier}{helvetica}%  
660 \MLX@@detectone{KurierCondHeavy}{Kurier}{helvetica}%  
661 \MLX@@detectone{lato}{Lato}{helvetica}%  
662 \MLX@@detectone{Lato}{Lato}{helvetica}%  
663 \MLX@@detectone{lmr}{lmodern}{lmodern}%  
664 \MLX@@detectone{mlmr}{MLModern}{lmodern}%  
665 \MLX@@detectone{mlmss}{MLModern}{lmodern}%  
666 \MLX@@detectone{lmss}{lmodern sans}{lmodernsans}%  
667 \MLX@@detectone{lmssq}{lmodern sans}{lmodernsans}%  
668 \MLX@@detectone{LatinModernRoman}{Latin Modern Roman}{lmodern}%  
669 \MLX@@detectone{LatinModernSans}{Latin Modern Sans}{lmodernsans}%  
670 \MLX@@detectone{LinuxLibertineT}{libertine}{libertine}%  
671 \MLX@@detectone{LinLibertine}{libertine}{libertine}%  
672 \MLX@@detectone{LinBiolinum}{libertine}{helvetica}%  
673 \MLX@@detectone{LibertinusSerif}{libertinus-type1}{libertinus}%  
674 \MLX@@detectone{LibertinusSans}{libertinus-type1}{helvetica}%  
675 \MLX@@detectone{libertinusserif}{libertinus-otf}{libertinus}%  
676 \MLX@@detectone{libertinusans}{libertinus-otf}{helvetica}%  
677 \MLX@@detectone{LibreBskvl}{librebaskerville}{baskerville}%  
678 \MLX@@detectone{LibreBaskerville}{librebaskerville}{baskerville}%  
679 \MLX@@detectone{LibreBodoni}{LibreBodoni}{librebodoni}%  
680 \MLX@@detectone{LibreCaslonText}{Libre Caslon}{baskerville}%  
681 \MLX@@detectone{LibreCsln}{Libre Caslon}{baskerville}%  
682 \MLX@@detectone{yly}{libris}{avantgarde}%  
683 \MLX@@detectone{llcmss}{LX Fonts}{avantgarde}%  
684 \MLX@@detectone{ptm}{mathptmx}{times}%  
685 \MLX@@detectone{ppl}{mathpazo}{palatino}%  
686 \MLX@@detectone{bch}{mdbch}{charter}%  
687 \MLX@@detectone{mdput}{mdput - Math Design Utopia}{utopia}%  
688 \MLX@@detectone{mdugm}{mdugm - Math Design URW Garamond}{baskerville}%  
689 \MLX@@detectone{Merriwthr}{merriweather}{merriweather}%  
690 \MLX@@detectone{MerriwthrSans}{merriweather}{merriweather}%  
691 \MLX@@detectone{Merriweather}{merriweather}{merriweather}%  
692 \MLX@@detectone{MerriweatherSans}{merriweather}{merriweather}%  
693 \MLX@@detectone{MintSpirit}{Mint Spirit}{avantgarde}%  
694 \MLX@@detectone{MintSpiritNoTwo}{Mint Spirit No 2}{avantgarde}%  
695 \MLX@@detectone{MintSpiritNo2}{Mint Spirit No 2}{avantgarde}%  
696 \MLX@@detectone{Montserrat}{Montserrat}{helvetica}%  
697 \MLX@@detectone{MontserratAlternates}{Montserrat}{helvetica}%  
698 \MLX@@detectone{pnc}{newcent}{newcent}%  
699 \MLX@@detectone{zpltlf}{newpertext}{palatino}%  
700 \MLX@@detectone{minntx}{newttext}{times}%  
701 \MLX@@detectone{ntxtlf}{newttext}{times}%  
702 \MLX@@detectone{nimbussans}{nimbussans}{helvetica}%

```

703 \MLX@@detectone{NimbusSans}{nimbusserif}{helvetica}%
704 \MLX@@detectone{NimbusSerif}{nimbusserif}{times}%
705 \MLX@@detectone{NimbusSansL}{nimbussans}{helvetica}%
706 \MLX@@detectone{ztm}{nimbusserif}{times}%
707 \MLX@@detectone{zhv}{nimbussans}{helvetica}%
708 \MLX@@detectone{NotoSerif}{noto}{noto}%
709 \MLX@@detectone{NotoSans}{noto}{noto}%
710 \MLX@@detectone{Nunito}{Nunito}{helvetica}%
711 \MLX@@detectone{OldStandard}{Old Standard}{didot}%
712 \MLX@@detectone{fosj}{opensans}{avantgarde}%
713 \MLX@@detectone{opensans}{opensans}{avantgarde}%
714 \MLX@@detectone{OpenSans}{Open Sans}{avantgarde}%
715 \MLX@@detectone{Zeroswald}{Oswald}{utopia}%
716 \MLX@@detectone{Ovrlck}{Overlock}{avantgarde}% bug with XeLaTeX%
717 \MLX@@detectone{Overlock}{Overlock}{avantgarde}% bug with XeLaTeX%
718 \MLX@@detectone{panr}{pandora}{pandora}%
719 \MLX@@detectone{pss}{pandora}{pandora}%
720 \MLX@@detectone{PTSerif}{paratype}{paratype}%
721 \MLX@@detectone{PTSans}{paratype}{paratype}%
722 \MLX@@detectone{PTSansNarrow}{paratype}{paratype}%
723 \MLX@@detectone{IBMPlexSerif}{plex-serif}{plexserif}%
724 \MLX@@detectone{IBMPlexSans}{plex-sans}{plexsans}%
725 \MLX@@detectone{pxr}{pxfonts}{palatino}%
726 \MLX@@detectone{pxss}{pxfonts}{helvetica}%
727 \MLX@@detectone{Quattro}{quattrocento}{quattrocento}%
728 \MLX@@detectone{QuattroSans}{quattrocento}{quattrocento}%
729 \MLX@@detectone{Quattrocento}{quattrocento}{quattrocento}%
730 \MLX@@detectone{QuattrocentoSans}{quattrocento}{quattrocento}%
731 \MLX@@detectone{Raleway}{raleway}{helvetica}%
732 \MLX@@detectone{Roboto}{roboto}{helvetica}%
733 \MLX@@detectone{RobotoSlab}{roboto}{roboto}%
734 \MLX@@detectone{RobotoCondensed}{roboto}{helvetica}%
735 \MLX@@detectone{yrd}{romande}{baskerville}%
736 \MLX@@detectone{yrda}{romande}{baskerville}%
737 \MLX@@detectone{yrdw}{romande}{baskerville}% todo swash style%
738 \MLX@@detectone{yrdaw}{romande}{baskerville}% todo swash style%
739 \MLX@@detectone{Shobhika}{Shobhika}{paratype}%
740 \MLX@@detectone{SourceSerifPro}{sourceserifpro}{sourceserifpro}%
741 \MLX@@detectone{SourceSansPro}{sourcesanspro}{sourcesanspro}%
742 \MLX@@detectone{SticksTooText}{stickstootext}{times}%
743 \MLX@@detectone{stix}{stix}{times}%
744 \MLX@@detectone{stix2}{stix2}{times}%
745 \MLX@@detectone{STIXTwoText}{stix2}{times}%
746 \MLX@@detectone{pbk}{bookman}{bookman}%
747 \MLX@@detectone{qbk}{tgbonum}{bookman}%
748 \MLX@@detectone{qhv}{tgheros}{helvetica}%
749 \MLX@@detectone{qpl}{tgpagella}{palatino}%
750 \MLX@@detectone{qcs}{tgschola}{newcent}%
751 \MLX@@detectone{qtm}{tgtermes}{times}%
752 \MLX@@detectone{TeXGyreAdventor}{TeX Gyre Adventor}{avantgarde}%
753 \MLX@@detectone{TeXGyreBonum}{TeX Gyre Bonum}{bookman}%
754 \MLX@@detectone{TeXGyreHeros}{TeX Gyre Heros}{helvetica}%
755 \MLX@@detectone{TeXGyrePagella}{TeX Gyre Pagella}{palatino}%
756 \MLX@@detectone{TeXGyreSchola}{TeX Gyre Schola}{newcent}%

```

```

757 \MLX@@detectone{TeXGyreTermes}{TeX Gyre Termes}{times}%
758 \MLX@@detectone{txr}{txfonts}{times}%
759 \MLX@@detectone{txss}{txfonts}{times}%
760 \MLX@@detectone{UniversalisADFStd}{Universalis ADF Std}{crimson}%
761 \MLX@@detectone{ugq}{URW Grotesk}{crimson}%
762 \MLX@@detectone{put}{utopia}{utopia}%
763 \MLX@@detectone{yvt}{venturis}{venturis}%
764 \MLX@@detectone{yvtj}{venturis}{venturis}%
765 \MLX@@detectone{yvtw}{venturis}{venturis}%
766 \MLX@@detectone{yvtjw}{venturis}{venturis}%
767 \MLX@@detectone{yvtaw}{venturis}{venturis}%
768 \MLX@@detectone{yvtajw}{venturis}{venturis}%
769 \MLX@@detectone{yv1}{venturissans}{venturis}%
770 \MLX@@detectone{yv2}{venturis2}{venturis}%
771 \MLX@@detectone{yv3}{venturissans2}{venturis}%
772 \MLX@@detectone{yvo}{venturissold}{venturis}%
773 \MLX@@detectone{yvoa}{venturissold}{venturis}%
774 \MLX@@detectone{XCharter}{XCharter}{charter}%
775 \MLX@@detectone{XITS}{XITS}{times}%

```

Warning if font was not found:

```

776 \ifbool{MLX@@foundfont}%
777   {}%
778   {%
779     \PackageWarningNoLine{metalogox}
780     {%
781       Did not find font \MLX@@thisfont.\MessageBreak
782       To improve \string\LaTeX, and related logos:\MessageBreak%
783       \string\usepackage[option]{metalogox}\MessageBreak%
784       Common options: times, bookman for serif,\MessageBreak%
785       helvetica, avantgarde for sans%
786     }
787   }
788 }

```

### 3.5 Option declaration

```

789 \DeclareOption*{%
790   \adjustlogos{\CurrentOption}%
791 }

```

### 3.6 Default settings

Adjust according to the text body font, if detected, or use defaults otherwise:

```

792 \autoadjustlogos*

```



### 3.7 Option trigger

Any metalogo package option will next override the above settings.

```
793 \ProcessOptions\relax
```

### 3.8 Support for the hologo and hvlogos packages

If hologo is used, a few macros are defined to use metalogo kerning. (hvlogos uses hologo, so is also supported.)

```
794 \AtBeginDocument{
795
796 \IfPackageLoadedTF{hologo}
797 {
798 \def\HoLogo@TeX#1{\TeX}
799
800 \def\HoLogo@La#1{%
801 \xL@everylogo
802 L\kern\xL@kern@La@La
803 {\ifxetex
804 \XeTeXuseglyphmetrics\@ne
805 \fi
806 \sbox\z@ T%
807 \sbox\@ne{\xL@LaTeX@a}%
808 \vbox to\ht\z@{%
809 \hbox{%
810 \ltx@sh@ft{\ht\z@}%
811 \xL@sh@ft{\ht\@ne}%
812 \xL@LaTeX@a
813 \xL@sh@ft{\ht\z@}%
814 \ltx@sh@ft{\ht\@ne}}%
815 \vss}}%
816 }
817
818 \def\HoLogo@LaTeX#1{\HoLogo@La{La}\kern\xL@kern@LaTeX@aT\TeX}
819
820 \def\HoLogo@LaTeXe#1{%
821 \hologo{LaTeX}%
822 \kern\xL@kern@LaTeXe@Xii%
823 \hbox{%
824 \HOLOGO@MathSetup
825 2%
826 $_{\textstyle\varepsilon}$%
827 }%
828 }
829
830 \def\HoLogo@LaTeXTeX#1{%
831 (%
832 \kern\xL@kern@LaTeX@aT
833 \hologo{La}%
```

```
834 \kern\xl@kern@LaTeX@aT
835 )%
836 \kern\xl@kern@LaTeX@aT
837 \hologo{TeX}%
838 }
839 \expandafter\let\csname HoLogo@(La)TeX\endcsname\HoLogo@LaTeXTeX
840
841 \def\HoLogo@XeTeX#1{\Xe\kern\xl@kern@XeTeX@eT\TeX}
842
843 \def\HoLogo@XeLaTeX#1{\Xe\kern\xl@kern@XeLaTeX@eL\LaTeX}
844
845 }
846 {}% hologo not loaded
847
848 }% AtBeginDocument
```

## A Change History

v1.00	Warning if font was not found. . . . .	17
General: 2019/01/20 Initial version. . . . .	\autoadjustlogos: Updated many	
v1.01	fonts for changed family names. . . . .	18
General: 2023/01/03 . . . . .	Warning if font was not found. . . . .	24
Docs adjusted for dtxdescribe. . . . .	\MLX@@detectvariant: Warning if	
Updated L <sup>A</sup> T <sub>E</sub> X Font Catalog	font was not found. . . . .	17
website. . . . .	v1.04	
v1.02	General: 2024/01/26 . . . . .	1
General: 2024/01/12 . . . . .	Added support for hologo, hvlogos. . . . .	25
Updated contact info. . . . .	v1.05	
v1.03	General: 2024/03/01 . . . . .	1
General: 2024/01/19 . . . . .	\autoadjustlogos: Fixed Erewhon. . . . .	18
Added Atkinson Hyperlegible,	v1.06	
Charis SIL, Cuprum, Eczar, Ibarra,	General: 2024/03/07 . . . . .	1
Inria, Inter, MLModern, Nunito,	\autoadjustlogos: Improved	
Oswald. . . . .	detection of Archiv0, Atkinson	
Improved TOC change log and	Hyperlegible, Cuprum, Eczar,	
index entries. . . . .	Ibarra, Nunito. . . . .	18

## B Index

<b>A</b>		concmath (option) . . . . .	16
accanthis (option) . . . . .	5	crimson (option) . . . . .	8
\adjustlogos . . . . .	3, 444	<b>D</b>	
alegreya (option) . . . . .	5	default (option) . . . . .	5
algorrevived (option) . . . . .	6	didot (option) . . . . .	8
antiqua (option) . . . . .	16	drm (option) . . . . .	16
antpolt (option) . . . . .	6	droidsans (option) . . . . .	9
anttor (option) . . . . .	16	droidserif (option) . . . . .	9
artemisia (option) . . . . .	16	<b>G</b>	
\autoadjustlogos . . . . .	4, 474	garamond (option) . . . . .	16
\autoadjustlogos <sub>␣</sub> * . . . . .	4	gentium (option) . . . . .	9
avantgarde (option) . . . . .	6	<b>H</b>	
<b>B</b>		helvetica (option) . . . . .	9
baskerville (option) . . . . .	6	<b>I</b>	
berenis (option) . . . . .	7	imfellenglish (option) . . . . .	16
bodoni (option) . . . . .	7	<b>K</b>	
boisik (option) . . . . .	7	kerkis (option) . . . . .	10
bookman (option) . . . . .	7	kpfonts (option) . . . . .	10
Booleans:		<b>L</b>	
MLX@@foundfont . . . . .	17	libertine (option) . . . . .	10
<b>C</b>		libertinus (option) . . . . .	10
caladea (option) . . . . .	16	librebodoni (option) . . . . .	11
caslon (option) . . . . .	16		
charter (option) . . . . .	8		
cochineal (option) . . . . .	16		
coelacanth (option) . . . . .	8		

literat (option) .....	17	noto .....	12
lmodern (option) .....	11	palatino .....	12
lmodernsans (option) .....	11	pandora .....	12
<b>M</b>			
merriweather (option) .....	11	paratype .....	13
metalogoX (package) .....	3	plexsans .....	13
\MLX@@detectone .....	461	plexserif .....	13
\MLX@@detectvariant .....	454	quattrocento .....	13
MLX@@foundfont (boolean) .....	17	roboto .....	17
<b>N</b>			
newcent (option) .....	12	romande .....	17
noto (option) .....	12	sourcesanspro .....	14
<b>O</b>			
Options:		sourceserifpro .....	14
accanthis .....	5	tgbonum .....	15
alegreya .....	5	tgheros .....	15
algotrevived .....	6	tgpagella .....	15
antiqua .....	16	tgschola .....	16
antpolt .....	6	tgtermes .....	16
anttor .....	16	times .....	14
artemisias .....	16	utopia .....	14
avantgarde .....	6	venturis .....	14
baskerville .....	6	vera .....	15
berenis .....	7	verasans .....	15
bodoni .....	7	<b>P</b>	
boisik .....	7	Packages:	
bookman .....	7	metalogoX .....	3
caladea .....	16	palatino (option) .....	12
caslon .....	16	pandora (option) .....	12
charter .....	8	paratype (option) .....	13
cochineal .....	16	plexsans (option) .....	13
coelacanth .....	8	plexserif (option) .....	13
concmath .....	16	<b>Q</b>	
crimson .....	8	quattrocento (option) .....	13
default .....	5	<b>R</b>	
didot .....	8	roboto (option) .....	17
drm .....	16	romande (option) .....	17
droidsans .....	9	<b>S</b>	
droidserif .....	9	sourcesanspro (option) .....	14
garamond .....	16	sourceserifpro (option) .....	14
gentium .....	9	<b>T</b>	
helvetica .....	9	tgbonum (option) .....	15
imfellenglish .....	16	tgheros (option) .....	15
kerkis .....	10	tgpagella (option) .....	15
kpfonts .....	10	tgschola (option) .....	16
libertine .....	10	tgtermes (option) .....	16
libertinus .....	10	times (option) .....	14
librebodoni .....	11	<b>U</b>	
literat .....	17	utopia (option) .....	14
lmodern .....	11	<b>V</b>	
lmodernsans .....	11	venturis (option) .....	14
merriweather .....	11	vera (option) .....	15
newcent .....	12	verasans (option) .....	15